

SAFETY DATA SHEET

1. Identification

Product identifier MAGNESIUM ALUMINATE SPINELS

Other means of identification

Synonyms MAE-10, MAE-26, MAE-32, MAET-26

Recommended use Refractory.

Recommended restrictions

Manufacturer/Importer/Supplier/Distributor information

Company Identification ELFUSA GERAL DE ELETROFUSÃO LTDA

Julio Michelazzo, 501 - São João da Boa Vista, São Paulo - Brasil - ZIP CODE 13872-900

Telephone +55.19.3634.2300

 Personal responsible for the SDS
 qualidade@elfusa.com.br

 Commercial
 comercial@elfusa.com.br

Homepagewww.elfusa.com.brContact personMr. Ruben SinatoEmergency telephone+55.11.99973.8421

E-mail ruben.sinato@grupocurimbaba.com.br

2. Hazard(s) identification

Physical hazards Not classified.
Health hazards Not classified.
OSHA defined hazards Not classified.

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The product does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS number	%		
Magnesium aluminum	oxide	Mixture	≥ 97		
Impurities:					
Other Oxides Total	-	N/A	≤ 3		
Constituents					
Chemical name	Common name and synonyms	CAS number	%		
Aluminum oxide		1344-28-1	64.5 - 90.5		
Magnesium oxide		1309-48-4	8.5 - 33		
Composition comments	All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. For more detailed chemical composition, refer to the certificate of analysis.				

4. First-aid measures

Inhalation Move to fresh air. Get medical attention if any discomfort continues.

Skin contactWash with soap and water. Get medical attention if irritation develops or persists. **Eye contact**Flush eyes thoroughly with water for at least 15 minutes. Get medical attention if

irritation develops or persists.

Immediately rinse mouth and drink plenty of water. Get medical attention if irritation

develops and persists.

Most important symptoms/effects, acute

and delayed

Irritation of eyes and mucous membranes. Irritation of nose and throat.



Indication of immediate medical attention

and special treatment needed.

Treat symptomatically.

General information

Get medical attention if any discomfort develops.

5. Fire-fighting measures

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media No restrictions known.

Specific hazards arising from the chemical

Special protective equipment and

precautions for firefighters

Firefighting equipment/instructions

General fire hazards

None known.

Self-contained breathing apparatus, operated in positive pressure mode and full

protective clothing must be worn in case of fire.

Move containers from fire area if you can do it without risk.

The product is not flammable.

6. Accidental release measures

Personal precautions, protective equipment

and emergency procedures

Methods and materials for containment and

cleaning up

Ensure adequate ventilation. Avoid inhalation of dust and contact with skin and eyes.

Wear protective clothing as described in Section 8 of this safety data sheet. Recover and recycle, if practical. Sweep up or vacuum up spillage and collect in suitable container for disposal. Do not vacuum clean unless vacuum cleaners are

equipped with HEPA filter.

Environmental precautions Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling

Provide adequate ventilation. Use work methods which minimize dust production. Avoid inhalation of dust and contact with skin and eyes. Wear appropriate personal

protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any

incompatibilities

Store in a dry place.

8. Exposure controls/personal protection

Occupational exposure limits

Magnesium oxide (CAS 1309-48-4)

Aluminum Oxide (CAS 1344-28-1)

US. OSHA Table Z-1 Limits for Air Contaminant	ts (29 CFR 1910.1000)	
Constituents	Type	Value	Form
Magnesium oxide (CAS 1309-48-4)	PEL	15 mg/m3	Total particulate
Aluminum Oxide (CAS 1344-28-1)	PEL	5 mg/m3 15 mg/m3	Respirable fraction. Total dust.
US. ACGIH Threshold Limit Values			
Material	Туре	Value	Form
Magnesium aluminum oxide (CAS Mixture)	TWA	1 mg/m3	Respirable fraction.
Constituents	Type	Value	Form

Biological limit values No biological exposure limits noted for the ingredient(s).

TWA

TWA

Exposure guidelines No exposure standards allocated.

Appropriate engineering controls Provide sufficient ventilation for operations causing dust formation. If engineering measures are

not sufficient to maintain concentrations of dust particulates below the Occupational Exposure

10 mg/m3

1 mg/m3

Inhalable fraction.

Respirable fraction.

Limit (OEL), suitable respiratory protection must be worn.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear goggles/face shield.

Skin protection

Hand protection Wear protective gloves. Suitable gloves can be recommended by the glove supplier.

Others Wear suitable protective clothing.

In case of inadequate ventilation or risk of inhalation of dust, use suitable respiratory Respiratory protection

equipment with particle filter. Seek advice from local supervisor.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Wash hands after handling. Routinely wash work clothing and protective equipment to remove

contaminants. Handle in accordance with good industrial hygiene and safety practice. Follow up

on any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Physical state Solid.

MAE-10, MAE-26, MAE-28, MAE-32, MAET-26 FS-4120-028 Version #: 04 Revision date: 05-September-2017 Issue date: 26-January-2012 2/6



Form Powder and grains.
Color Beige or white.
Odor Odorless.
Odor threshold Not available.
pH 6 - 9.5

Melting point/freezing point3875°F (2135°C)Initial boiling point and boiling rangeNot availableFlash pointNot availableEvaporation rateNot applicableFlammability (solid, gas)Non flammable

Upper/lower flammability or explosive limits

Flammability limit-lower (%)
Flammability limits-upper (%)
Explosive limit-lower (%)
Explosive limit-upper (%)
Vapor pressure
Vapor density
Relative density

Not available
Not available
Not applicable
Not applicable
3 - 3.4

Solubility (ies)

Solubility (water)Not availablePartition coefficient (n-octanol/water)Not applicableAuto-ignition temperatureNot applicableDecomposition temperatureNot availableViscosityNot applicable

Other information

Bulk densityNot applicableExplosive propertiesNot explosiveOxidizing propertiesNot oxidizing

10. Stability and reactivity

Reactivity The product is stable and non reactive under normal conditions of storage and

transport.

Chemical stability Stable at normal conditions.

Possibility of hazardous reactions Hazardous polymerization does not occur. Hazardous reactions do not occur.

Conditions to avoid Moisture. Contact with incompatible materials.

Incompatible materials None known.

Hazardous decomposition productsNo hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Dust may irritate respiratory system.

Skin contactDust may irritate skin.Eye contactDust may irritate the eyes.

Ingestion Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical

and toxicological characteristics Information on toxicological effects Irritation of eyes and mucous membranes. Irritation of nose and throat.

Acute toxicity

Dust may cause eye, skin and respiratory tract irritation.

Product Species Test Results

Magnesium aluminum oxide (CAS Mixture)

Acute Oral

LD50 Rat > 5000 mg/kg

Constituents Species Test Results

Aluminum oxide (CAS 1344-28-1)

Acute Inhalation

LC50 Rat > 2.3 mg/l, 4 horas

Oral

LD50 Rat > 5000 mg/kg

MAE-10, MAE-26, MAE-28, MAE-32, MAET-26

FS-4120-028 Version #: 04 Revision date: 05-September-2017 Issue date: 26-January-2012 3/6



Skin corrosion/irritation May cause irritation through mechanical abrasion. Serious eye damage/eye irritation May cause irritation through mechanical abrasion.

Respiratory or skin sensitization

Respiratory sensitization Not classified. Skin sensitization Not a skin sensitizer.

Germ cell mutagenicity Test data conclusive but not sufficient for classification. Carcinogenicity Test data conclusive but not sufficient for classification.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

NTP Report on Carcinogens

Not listed

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Reproductive toxicity Test data conclusive but not sufficient for classification. Specific target organ toxicity-single exposure Test data conclusive but not sufficient for classification.

Specific target organ toxicity-repeated

exposure

Test data conclusive but not sufficient for classification.

Not classified. **Aspiration hazard**

Chronic effects Prolonged and repeated overexposure to dust can lead to pneumoconiosis. **Further information** Prolonged and repeated overexposure to dust can lead to pneumoconiosis.

12. Ecological information

This product has no known eco-toxicological effects. The product is not expected to **Ecotoxicity**

be hazardous to the environment. The product is not biodegradable.

Persistence and degradability Bioaccumulative potential The product is not bioaccumulating.

Mobility in soil Aluminum oxide is not mobile in the environment, unless it comes into contact with

an aqueous environment with a pH below 5.5 or above 8.5.

Mobility in general The product is insoluble in water.

Other adverse effects Not expected to be harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions Dispose in accordance with all applicable regulations.

Hazardous waste code Not regulated.

Waste from residues / unsed products Recover and recycle, if practical. Dispose of in accordance with local regulations.

Contaminated packaging Offer rinsed packaging material to local recycling facilities. Dispose of in accordance

with local regulations.

14. Transport information

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not available.

15. Regulatory information

US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

MAE-10, MAE-26, MAE-28, MAE-32, MAET-26

FS-4120-028 Issue date: 26-January-2012 4/6 Version #: 04 Revision date: 05-September-2017



Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical - No

SARA 313 (TRI reporting)

 Chemical name
 CAS number
 % by wt.

 Aluminum oxide (CAS 1344-28-1)
 1344-28-1
 64.5 - 90.5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated (SDWA)

Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Aluminum oxide (CAS 1344-28-1)

Magnesium oxide (CAS 1309-48-4)

US. New Jersey Worker and Community Right-to-Know Act

Aluminum oxide (CAS 1344-28-1)

Magnesium oxide (CAS 1309-48-4)

US. Pennsylvania Worker and Community Right-to-Know Law

Aluminum oxide (CAS 1344-28-1) Magnesium oxide (CAS 1309-48-4)

US. Rhode Island RTK

Aluminum oxide (CAS 1344-28-1)

US. California Proposition 65

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date26-January-2012Revision date05-September-2017

Version 4

MAE-10, MAE-26, MAE-28, MAE-32, MAET-26

FS-4120-028 Version #: 04 Revision date: 05-September-2017 Issue date: 26-January-2012 5/6

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country (s).



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently

HMIS® ratings Health = 1

Flammability = 0Physical Hazard = 0

References

List of Abbreviations

available.

NFPA ratings



IUCLID

Chemical safety report. LD50: Lethal Dose, 50%.

LC50: Lethal Concentration, 50%.